

POLYBLOC[®] TSR

THERMAL STRESS RESISTANT

ANTICORROSION EQUIPMENT

Mersen's new Polybloc[®] TSR (patent pending) offers a **greatly** improved resistance to thermal shocks.

This design **reduces the mechanical stress induced by thermal shock by a factor exceeding 3** and thus considerably reduces the risk of breakage.

(1) stands for "Thermal stress Resistant"



Background on Polybloc® heat exchangers and Graphilor® graphite

Mersen's Polybloc® heat exchangers comprise of cylindrical blocks of Graphilor® BS, XBS, XTH, or XC, manufactured from either an extruded or an isostatic graphite, impregnated with either phenolic resin, PTFE or carbon.

Graphilor® is well known for its outstanding corrosion resistance, high thermal conductivity and superior mechanical properties. Polybloc® heat exchangers offer sturdy and modular solutions in ultra-corrosive applications.

Block cracking due to thermal shock during condensation

Notwithstanding the superior properties of Graphilor®, **significant thermal shocks can trigger mechanical stresses** such that the blocks can **crack**.

Let's take the example of a graphite condenser located above a fine chemical process reactor: the hot vapors condense in the holes on the process side, while the cooling fluid, usually chilled water, circulates in the shell on the service side. If the user feeds the process side with vapors at a temperature between 80°C and 100°C, and suddenly feeds the service side with chilled water at 5°C, the graphite is likely to suffer a thermal shock, which could lead to the cracking of one or more blocks in condenser.

The higher the difference between the temperature of the service side fluid and the inlet temperature on the process side, the greater the thermal shock and the greater the risk of block damage.

Mersen Polybloc® TSR heat exchangers

Mersen has developed a new block design, called **Polybloc® TSR** (patent pending), offering a **greatly improved resistance to thermal shocks**. This design **reduces the mechanical stresses induced by thermal shock by a factor exceeding 3 and thus considerably reduces the risk of breakage**.

All new Polybloc® TSR remain **fully compatible and interchangeable** with all Polybloc® exchanger blocks marketed by Mersen. They are offered in Graphilor® BS, XBS, XTH or XC and for **each drilling diameter and pattern currently available**.

HOW TO CONTACT US

Mersen Pagny-sur-Moselle

Tel.: +33 (3) 83 81 60 81

✉ Info.pagny@mersen.com