



RATING	CATALOG NO.
10E	A055F1DOR0-10E
15E	A055F1DOR0-15E
20E	A055F1DOR0-20E
25E	A055F1DOR0-25E
30E	A055F1DOR0-30E
40E	A055F1DOR0-40E
50E	A055F1DOR0-50E
65E	A055F1DOR0-65E
80E	A055F1DOR0-80E
100E	A055F1DOR0-100E
125E	A055F1DOR0-125E
150E	A055F1DOR0-150E
175E	A055F1DOR0-175E
200E	A055F1DOR0-200E

SURFACE "A" →

INDICATOR FLUSH WITH SURFACE "A" BEFORE FUSE OPENS.  
 INDICATOR EXTENDS .50in(12.7mm) AFTER FUSE OPENS.  
 INDICATOR EXERTS 2 LB FORCE AT END OF TRAVEL

**GOULD** 374 MERRIMAC STREET  
 NEWBURYPORT, MA 01950

PRODUCT MANAGER

DESIGN ENGINEER

SIGN:  
 DATE:

SIGN:  
 DATE:

MEDIUM VOLTAGE AMP-TRAP  
 E-RATED GENERAL PURPOSE  
 CURRENT LIMITING FUSE  
 CS-3 SERIES, 10E TO 200E, 5.5KV MAX

OUTLINE DIMENSIONS  
 NOT TO BE USED FOR PRODUCTION

24391